



EVO2000 Hyper Series

單模組

350W~600W

Support 180-518V AC

Up to 170 lm/w

支援智能燈控

技術規格

技術規格						
型號	EVO2350PLX	EVO2400PLX	EVO2450PLX	EVO2500PLX	EVO2550PLX	EVO2600PLX
輸出功率	350W±5%	400W±5%	450W±5%	500W±5%	550W±5%	600W±5%
LED晶片	OSRAM 					
演色性	≥70 (Cool White), >=80 (Natural & Warm White), >=90 (optional)					
晶片數	230pcs					
光通(白光)	≥60,000 lm ≥ 170 lm/w	≥67,200 lm ≥ 168 lm/w	≥72,900 lm ≥ 160 lm/w	≥80,000 lm ≥ 160 lm/w	≥86,000 lm ≥ 158 lm/w	≥93,000 lm ≥ 155 lm/w
電源	MeanWell XLG-200, 100~305V AC, 0-10V Dimmable x2		MeanWell XLG-240 100~305V AC,0-10V Dimmable x2		MeanWell XLG-320 100~305V AC,0-10V Dimmable x2	
可選用高電壓電源	MeanWell HVG-350H, 180-518V AC, 1-10V x1	MeanWell HVG-240H, 180-518V AC, 1-10V x2	MeanWell HVG-240H, 180-518V AC, 1-10V x2		MeanWell HVG-320H, 180-518V AC, 1-10V x2	
調光介面	0-10V (XLG), 1-10V (HLG/HVG)					
工作溫度範圍	-40°C~55°C, indoors and outdoors					
IP等級	IP66					
出光角	15°/30°/45°/60°/90°, PC AIO Lens Tear-Drop Technology					
色溫	5000K(CW)/4000K(NW)/ 2700K(WW)					
尺寸	561x293x146mm (含支架)					
重量	10.5 Kg		12.5 Kg		14.5 Kg	
材質	鋁合金壓鑄散熱本體/工業灰戶外專用烤漆 AIO一體成型PC透鏡組/抗UV處理 支架材質304不銹鋼					
工業規範	1000小時塩霧測試 (ASTM B117) 17級風壓測試 3G抗震					
智能控制支援	支援ECO-Link/ PowerLink控制系統(選購) 支援DALI或DMX(另洽)					
保固	5 Years, Life Span>=50,000 hrs					
產地	Made in Taiwan					
認證	CE/CNS/ROHS/BSMI/節能標章					

