



EVO 2000 M-Type
全新世代中功率
200W~320W
最高達 170 lm/w
工業等級設計

支援智能控制系統

規格

型號	EVO 2320PLM	EVO 2280PLM	EVO 2250PLM	EVO 2220PLM	EVO 2200PLM			
額定功率	320W±10%	280W±10%	250W±10%	220W±10%	200W±10%			
LED晶片	OSRAM							
演色性	>70, (>80 選購)							
顆粒數	336pcs							
總光通量 發光效率	> 51,200 lm > 160 lm/W	> 47,600 lm > 170 lm/W	> 42,500 lm > 170 lm/W	> 37,840 lm > 172 lm/W	> 34,400 lm > 172 lm/W			
電源	MEANWELL XLG-320		MEANWELL XLG-240					
AC輸入	100 ~ 277V, 50/60Hz							
調光	0 ~ 10V							
工作溫度	-40°C~50°C, indoors and outdoors							
IP等級	IP66							
出光角	15° / 30° / 45° / 60°, PC AIO 透鏡 Tear-Drop Technology							
色溫	5000K±10% (白光) / 4000K±10% (暖白光) / 3000K±10% (黃光)							
尺寸	414mm * 276mm * 168mm (含支架及電源箱)							
淨重	6.6 Kg		6.2 KG					
材質	高強度鋁合金壓鑄 / 工業灰粉體烤漆 高透光抗UV, 光學級PC透鏡 不銹鋼SUS304直式支架及斜式支架							
工業認証	1000小時塩霧測試 17級風 風洞測試 3G抗震動測試 IK10 / IP66等級 / 光生物安全測試							
智能控制	支援Neotroni ECO-Link及PowerLink燈光控制系統 亦可加裝DALI或DMX燈控器							
突波保護	10 kV/5kA							
保固	5年保固							
產地	Made in Taiwan							
國際認証	CNS / BSMI / CE / ROHS							

