



EVO2000 Hyper Series

三模組

1350W/1500W/1650W/1800W

Support 180-518V AC

Up to 160 lm/w

支援智能燈控

技術規格

技術規格				
型號	EVO21K3PLX	EVO21K5PLX	EVO21K6PLX	EVO21K8PLX
輸出功率	1350W±5%	1500W±5%	1650W±5%	1800W±5%
LED晶片	OSRAM 			
演色性	≥70 (Cool White), >=80 (Natural & Warm White), >=90 (optional)			
晶片數	690pcs			
光通量(白光)	≥119,000 lm ≥ 160 lm/w	≥134,400 lm ≥ 160 lm/w	≥144,000 lm ≥ 158 lm/w	≥160,000 lm ≥ 155 lm/w
電源	MeanWell XLG-240, 100~305V AC, 0-10V Dimmable x6		MeanWell XLG-320 100~305V AC,0-10V Dimmable x6	
可選用高電壓電源	MeanWell HVG-240H, 180-518V AC, 1-10V Dimmable x6		MeanWell HVG-320H, 180-518V AC, 1-10V Dimmablex6	
調光介面	0-10V (XLG), 1-10V (HLG/HVG)			
工作溫度範圍	-40°C~55°C, indoors and outdoors			
IP等級	IP66			
出光角	15°/30°/45°/60°/90°, PC AIO Lens Tear-Drop Technology			
色溫	5000K(CW)/4000K(NW)/ 2700K(WW)			
尺寸	633x832x441mm (include Tilt bracket)			
重量	42 Kg		46 Kg	
材質	鋁合金壓鑄散熱本體/工業灰戶外專用烤漆 AIO一體成型PC透鏡組/抗UV處理 支架材質304不銹鋼			
工業規範	1000小時塩霧測試 (ASTM B117) 17級風壓測試 3G抗震			
智能控制支援	支援ECO-Link/ PowerLink控制系統(選購) 支援DALI或DMX(另洽)			
保固	5 Years, Life Span>=50,000 hrs			
產地	Made in Taiwan			
認證	CE/CNS/ROHS			

