



EVO2000 Hyper Series

雙模組

700W~1200W

Support 180-518V AC

Up to 170 lm/w

支援智能燈控

技術規格

型號	EVO2700PLX	EVO2800PLX	EVO2900PLX	EVO21K0PLX	EVO21K1PLX	EVO21K2PLX
輸出功率	700W±5%	800W±5%	900W±5%	1000W±5%	1100W±5%	1200W±5%
LED晶片	OSRAM					
演色性	≥70 (Cool White), >=80 (Natural & Warm White), >=90 (optional)					
晶片數	460pcs					
光通量(白光)	≥119,000 lm ≥ 170 lm/w	≥134,400 lm ≥ 168 lm/w	≥144,000 lm ≥ 160 lm/w	≥160,000 lm ≥ 160 lm/w	≥173,000 lm ≥ 158 lm/w	≥186,000 lm ≥ 155 lm/w
電源	MeanWell XLG-200, 100~305V AC, 0-10V Dimmable x4		MeanWell XLG-240 100~305V AC,0-10V Dimmable x4		MeanWell XLG-320 100~305V AC,0-10V Dimmable x4	
可選用高電壓電源	MeanWell HVG-350H, 180-518V AC, 1-10V x2	MeanWell HVG-240H, 180-518V AC, 1-10V x4			MeanWell HVG-320H, 180-518V AC, 1-10V x4	
調光介面	0-10V (XLG), 1-10V (HLG/HVG)					
工作溫度範圍	-40°C~55°C, indoors and outdoors					
IP 等級	IP66					
出光角	15°/30°/45°/60°/90°, PC AIO Lens Tear-Drop Technology					
色溫	5000K(CW)/4000K(NW)/ 2700K(WW)					
尺寸	663x545x146mm (include Straight bracket) 663x545x294mm (include Tilt bracket)					
重量	29.5 Kg	30.5 Kg			32 Kg	
材質	鋁合金壓鑄散熱本體/工業灰戶外專用烤漆 AIO一體成型PC透鏡組/抗UV處理 支架材質304不銹鋼					
工業規範	1000小時鹽霧測試 (ASTM B117) 17級風壓測試 3G抗震					
智能控制支援	支援ECO-Link/ PowerLink控制系統(選購) 支援DALI或DMX(另洽)					
保固	5 Years, Life Span>=50,000 hrs					
產地	Made in Taiwan					
認證	CE/CNS/ROHS/BSMI/節能標章*(部份機型)					

